

ENVIRONMENTAL TESTERS

Sound Level Meter







Model CA832

Designed to assess sound ambiences or nuisances in accordance with international safety and quality standards

► SPECIFICATIONS

MODEL	CA832
MEASUREMENTS	
Measurement Range	35 to 80dB 50 to 100dB 80 to 130dB
Measurement Rate	2.5 times per second
Dynamic Range	50db
Frequency Range	31.5 to 8000Hz
Accuracy	±1.5dB (ref. 94dB@1kHz)
Resolution	0.1dB
Precision	±2.0dB
Display	2000-count
Sensor Type	0.5" electric (prepolarized) condenser microphone True RMS measurement with independent frequency weighting
Applicable Standard	IEC 651 type 2/ANSI S 1.4 type 2/JIS C 1502
Auxiliary Output	DC output: $10\text{mV/dB} - 50\Omega$ AC output: $1.0\text{Vrms} - 600\Omega$
Frequency Weighting	Curves A and C
Time Weighting	S (slow) and F (fast)
GENERAL	
Display	3½ digit liquid crystal display (LCD), 2000-count
Operating Temperature	32° to 122°F (0° to 50°C), 80% RH without condensation
Storage Temperature	-4° to 140°F (-20° to 60°C), 0 to 80% RH without battery
Power Source	One 9V Alkaline battery (included)
Low Battery Indication	- +1 is displayed when battery voltage is low
Dimensions	9.33 x 2.38 x 1.5" (237 x 60.5 x 38mm)
Weight	8.11 oz (230g) including battery





 $C \in$

► FEATURES

- · Easy one-hand operation
- · Measures sound according to the sensitivity of the human ear
- Max function
- Three measurement ranges from 35 to 130dB
- Accuracy ±1.5dB (ref. 94dB@1kHz)
- Two time weighting curves: S (slow) - 550ms and F (fast) - 55ms
- Two frequency weighting curves: A and C
- · Auxiliary output for recording
- Tripod mountable
- 2000-count backlit LCD
- · Lightweight and compact
- · Includes rugged, shockproof, protective and dirt resistant gray holster

►APPLICATIONS

- Factories
- Schools and Libraries
- Airports
- · Office environments and Studios
- Auditoriums
- Hospitals

CATALOG NO. DESCRIPTION

2121.23 Sound Level Meter Model CA832