



NEW!

Users can be sure of  
working in a higher degree  
of safety with 1000V CAT IV  
rated meters



## ► FEATURES

- 1000V CAT IV Rated
- UL 94 VI flame retardant self-extinguishing
- IP54 Rated
- 10,000 count blue electroluminescent backlit display
- Measures up to 1000VAC (1400V peak), 1000VDC and AC+DC with resolution to 10mV
- Measures up to 2000AAC and 3000ADC (model dependent)
- Measures single- and three-phase power (real, reactive and apparent) up to 3MW with resolution to 1W (model dependent)
- Measures frequency to 20kHz with 0.1Hz resolution
- Auto selects AC or DC measurement voltage
- True InRush™ current measurement with 1mS capture
- Jaw opening up to 1.89" (400 series) and up to 2.36" (600 series)
- Leads are constructed with a flexible silicone material

## ► SPECIFICATIONS

MODELS	401/601 TRMS	403/603 TRMS	405/605 TRMS
<b>ELECTRICAL</b>			
Current AC (rms)	1000/2000A	1000/2000A	1000/2000A
Current DC	—	1500/3000A	1500/3000A
Current AC+DC	—	—	1500/3000A
Voltage AC (rms)	1000/1000V	1000/1000V	1000/1000V
Voltage DC	1000/1000V	1000/1000V	1000/1000V
Voltage AC+DC	—	—	1000/1000V
Ohms	100/100kΩ	100/100kΩ	100/100kΩ
Continuity (Buzzer)	Yes (< 40Ω)	Yes (< 40Ω)	Yes (< 40Ω)
Diode Test	Yes	Yes	Yes
Total Harmonic Distortion	—	—	Yes
Single- and 3-Phase Real Power (AC, DC, AC/DC)*	—	—	1000/2000kW 3000/6000kW
Single- and 3-Phase Reactive Power (AC, DC, AC/DC)*	—	—	1000/2000kvar 3000/6000kvar
Single- and 3-Phase Apparent Power (AC, DC, AC/DC)*	—	—	1000/2000kVA 3000/6000kVA
Temperature (int., ext., C°, F°)	Yes	Yes	—
Voltage Frequency (Hz)	20kHz	20kHz	20kHz
Current Frequency (Hz)	Models 400 Series: 2kHz, Models 600 Series: 1kHz		
Power Function	—	—	Yes
THD-r/THD-f	—	—	Yes
Adapter (AC/DC)	—	0-10V	—
Phase Rotation	—	—	Yes (2 threads)
Auto AC/DC	Yes (V)	Yes (V & A)	Yes (V & A)
Auto Power OFF	Yes	Yes	Yes
Hold Button	Yes	Yes	Yes
Backlight Button	Yes	Yes	Yes
Min/Max Button	Yes	Yes	Yes
True InRush™ Function	Yes	Yes	Yes
Relative Function	—	Yes	Yes
Peak ± Function	—	—	Yes
Hz Button	Yes	Yes	Yes
Jaw Opening Size (Diameter)	1.89"/2.36"	1.89"/2.36"	1.89"/2.36"
Protection Index	Housing: IP54 (per standard IEC-60529)/Jaws: IP40		

\*3-phase measurements assume balanced load

## CATALOG NO.

## DESCRIPTION

2139.20	Clamp-On Meter Model 401 (TRMS, 1000VAC/DC, 1000AAC, Ohms, Continuity, Temperature)
2139.21	Clamp-On Meter Model 403 (TRMS, 1000VAC/DC, 1000AAC/1500ADC, Ohms, Continuity, Temperature)
2139.50	Power Clamp-On Meter Model 405 (TRMS, 1000VAC/DC, 1000AAC/1500ADC, Ohms, Continuity, Power, THD)
2139.30	Clamp-On Meter Model 601 (TRMS, 1000VAC/DC, 2000AAC, Ohms, Continuity, Temperature)
2139.31	Clamp-On Meter Model 603 (TRMS, 1000VAC/DC, 2000AAC/3000ADC, Ohms, Continuity, Temperature)
2139.60	Power Clamp-On Meter Model 605 (TRMS, 1000VAC/DC, 2000AAC/3000ADC, Ohms, Continuity, Power, THD)