GFM-200A-DM

Ground Bond Tester



*Image for reference only

3-200A Laboratory/Engineering High Current Ground Continuity Tester.

A Compliance West ground bond tester. Equipped with Amp and Volt digital meters. Tester is designed to output 300A with a max load of 0.010Ω output. Premium leads and alligators for high performance. Front output breaker switch and large knob for easy adjustment.

Built in the USA. Email and phone support free for life. Reasonable repair and calibration charges. Timely and helpful customer service always.

Features

- Ideal for testing spot welds, bus bars, grounding straps, cables, chassis and other high current devices.
- AC Output. Adjustable current from 0-300A to any ground circuit with resistance of 0-10m Ω.
- Four-wire output voltage sensing compensates for lead resistance.
- High efficiency design results in less power consumption.
- Ergonomically designed for safety, speed and efficiency.

- Digital Meters for Current and Voltage.
- Red Flashing backlight alarm indicates output over 305A.
- Front Panel output breaker switch.
- Flexible leads with clamps for high current.
- Large Knob for easy output adjustment.
- Power cables, manual and calibration certificate included.
- One year calibration cycle & one year warranty.
- Ships with ANSI Cal, ILAC Cal available.



techniCAL 866-327-8731 www.techniCAL-sys.com



GFM-200A-DM

Specifications

Test Type:	AC.
Current Output:	3-300Aac (Short circuit) *Do not exceed 200A 3-200Aac (Short circuit to 10.0mΩ.) Duty Cycle 50%, two minutes on, two minutes off.
Max. Voltage Output:	4.75Vac (Open Circuit)
Current Meter:	3.0-30.0Aac ±5% 30.0-300.0Aac ±2.5%
Voltage Meter:	0.37-6.0Vac ±1.5%
Alarm trigger:	205.0Aac
Input Power (120V version):	120V 10.0A (Short circuit to 10.0mΩ.)
Input Power (220V version):	220V 5.0A (Short circuit to $10.0m\Omega$.)

Environmental

Operating Temperature:	15-28ºC, 60-95ºF
Relative Humidity Range:	0-90% non-condensing

General

N

D:	
Dimen	isinns'

Weight:

techniC/

866-327-8731 www.techniCAL-sys.com

Product Package:

11.25" (W) x 6.75" (H) x 13.00" (L)

55 lbs approx.

- GFM-300A-DM 120V.
- GFM-300A-DM Product Manual.
- AC Power Cord.
- 4 wire sense leads with clamps.



