

DATA SHEET

SI-AQ VOC

Handheld TVOCs Monitor for Air Quality Analysis in Industrial Safety, Environmental, Laboratories and More

Accurate / Reliable / Robust / Fast

- Dynamic PID TVOC Sensor:
0 - 20,000 ppb or 0 - 200 ppm
- Temp., %RH, & Barometric Pressure Included
- Real-Time Data Logging
- Active Internal Sampling Pump
- Large Internal Memory (2,000 Tests)
- Protective Magnetic Rubber Boot
- Optional Wireless Printer
- Optional Handheld Probe



Select Up to 3 Gases in Total:
TVOCs, CO₂, CO, Formaldehyde, NO₂,
NO, O₂, SO₂, H₂S



Long Lasting Rechargeable Battery & AC Charger



Light Weight & Durable



Si-AQ PCSoft PC Software & USB Cable

Parameter	Sensor	Range	Resolution	Accuracy
Low Range VOC OR High Range VOC	PID	0 - 20,000 ppb 0 - 46,000 µg/m ³	1 ppb 1 µg/m ³	±10 % rdg ±20 ppb
Relative Humidity	TFC	5 - 95 %	0.1 %	±2 % RH
Ambient Temperature	Pt100	-40 to 257 °F -40 to 125 °C	0.1 °F 0.1 °C	±0.4 °F (32 - 140 °F) ±0.4 °C (0 - 60 °C)
Barometric Pressure	Solid state	260 to 1,260 mbar	1 mbar	±2 mbar
Differential Pressure	Bridge	0 - 32.0 inH ₂ O 0 - 80.0 mbar	0.1 inH ₂ O 0.1 mbar	±1 % rdg
Temperature Type K T1	Tc K	0 - 2,000 °F 0 - 1,100 °C	1 °F 1 °C	5 °F / 3 °C or 2 % rdg
Air Velocity	Calculated	0 - 300 ft/sec 0 - 91 m/s	1 ft/sec 1 m/s	-
Electromagnetic Compatibility	EN 61326-1, Portable Equipment			

All Si-AQ VOC Kits include:

- Temperature, %RH, Wet Bulb, Dew Point
- Barometric Pressure
- PC Software & USB Cable
- Real-Time Continuous Data Logging
- Bluetooth® Connectivity
- Protective Carrying Case
- Continuous Active Internal Sampling Pump
- Long Lasting Battery & AC Charger
- Factory Calibration Certificate
- Quick Start Guide

Optional Accessories




Sampling Probe
(Si-AQ Probe with Hose)



Zero Filter for Calibration
(Si-AQ VOC Zero Filter)



Bluetooth® Printer
(Si-AQ Bluetooth® Printer)



Moisture Exchange
Tube for Calibration
(Si-AQ Moisture Exchange)

Si-AQ VOC Ordering Code

Example: Part #: VOC - Si-AQ VOC Cell (20,000 ppb) - Si-AQ CH₂O Cell (0 - 10 ppm) - Si-AQ CO₂ Sensor (5000 ppm) = Low Range VOC, CH₂O & CO₂

	Parameter	Sensor	Range	Resolution	Accuracy
Select Your VOC Range	Si-AQ VOC Cell (20,000 ppb) Low Range VOC	PID	0 - 20,000 ppb 0 - 46,000 µg/m ³		
	Si-AQ VOC Cell (200 ppm) High Range VOC	PID	0 - 200 ppm 0 - 460 mg/m ³		
Optional Gas Sensor Upgrades (Choose Up to Any 2)	Si-AQ CO ₂ Sensor (5000 ppm) Carbon Dioxide (CO ₂) ¹	NDIR	0 - 5,000 ppm	1 ppm	±2 % rdg ±10 ppm
	Si-AQ CO Cell (0 - 200 ppm) Carbon Monoxide (CO) ¹	EC ²	0 - 200 ppm	0.1 ppm	±4 % rdg ±0.5 ppm
	Si-AQ CH ₂ O Cell (0 - 10 ppm) Formaldehyde (CH ₂ O) ^{3,4}	EC ²	0 - 10,000 ppb	1 ppb	±5 % rdg ±50 ppb
	Si-AQ H ₂ S Cell (0 - 100 ppm) Hydrogen Sulfide (H ₂ S) ¹	EC ²	0 - 100 ppm	1 ppm	±4 % rdg ±0.5 ppm
	Si-AQ NO ₂ Cell (0 - 20 ppm) Nitrogen Dioxide (NO ₂) ¹	EC ²	0 - 20 ppm	0.1 ppm	±4 % rdg ±0.5 ppm
	Si-AQ O ₂ Cell (0 - 25 %) Oxygen (O ₂)	EC ²	0 - 25 %	0.1 %	±0.1 % vol rdg
	Si-AQ SO ₂ Cell (0 - 20 ppm) Sulfur Dioxide (SO ₂) ¹	EC ²	0 - 20 ppm	0.1 ppm	±4 % rdg ±0.5 ppm
	Si-AQ NO Cell (0 - 250 ppm) Nitric Oxide (NO) ¹	EC ²	0 - 250 ppm	0.1 ppm	±4 % rdg ±0.5 ppm

¹ Other ranges are available upon request

² Electrochemical

³ Accuracy based on laboratory conditions

⁴ This sensor may have interference from H₂, CO, H₂S and other reducing gases such as alcohols